



Fabric Collection for Roller Blinds

Flame Retardant, Anti-Bacteria & Lead free

Specification – Sunscreen Fabric for Roller Blinds

Features	SS 914	SS 901	SS 918	SS 904	SS 950	SS 902
	SS 915	SS 906	SS 919	SS 905	SS 951	SS 903
	SS 916	SS 910	SS 920	SS 906	SS 952	SS 911
	SS 917	SS 970	* SS 927	SS 907	SS 953	SS 913
		SS 971	* SS 928	SS 908	SS 954	SS 921
		SS 972	* SS 929	SS 909	SS 955	SS 922
		SS 973	* SS 930	SS 912	SS 956	SS 923
		SS 974		SS 941	SS 957	SS 924
				SS 942	SS 958	SS 925
				SS 943	SS 959	SS 926
				SS 944	SS 960	
	(Premium)		(Premium)			
Composition	30% Polyester & 70% PVC					
Fabric Width (cm)	250 & 300					
Openness Factor (%)	1	3	3	5	5	
Thickness (mm)	0.96 ± 5%	0.62 ± 5%	0.62 ± 5%	0.68 ± 5%	0.70 ± 5%	
Weight (g/m ²)	690 ± 5%	430 ± 5%	430 ± 5%	500 ± 5%	550 ± 5%	
Flame Retardant	NFPA 701:2015 TM#2, BS5867 Part 2 Type B, DIN 4102-1 B1					
Colour Fastness	ISO 105 B02, Grade 8					
UV Blockage	± 97%					
Bacteria & Fungal Resistance	ASTM G21					
Lead Free	16 CFR 1303 (USA)					
Environmental Certification	GREENGUARD Gold Certification					
Silver Backing	No	No	* Yes	No	No	No
Internal Application	Yes	Yes	Yes	Yes	Yes	Yes
External Application	No	No	No	No	No	Yes



PRODUCT CERTIFIED FOR
LOW CHEMICAL EMISSIONS
UL.COM/CGG
UL 2818






SS 901



SS 902



SS 903



SS 904



SS 905




SS 906




SS 907



SS 908



SS 909



SS 910



SS 911




SS 912



SS 913




SS 914



SS 915




SS 916



SS 917




SS 918




SS 919



SS 920



SS 921



SS 922



SS 923



SS 924



SS 925



SS 926



SS 927



SS 928




SS 929



SS 930




SS 941



SS 942



SS 943




SS 944



SS 950



SS 951



SS 952



SS 953



SS 954



SS 955



SS 956



SS 957



SS 958



SS 959



SS 960



SS 970



SS 971



SS 972



SS 973



SS 974

Specification – Blackout Fabric for Roller Blind

A 100% blackout fabric suitable for Roller & Panel Track Blinds. Serial offers a classic neutral color range with an opaque finish. It is PVC free, has anti fade, easy clean & antifungal properties. It is flame retardant to international standards.



Lightfastness >6.0



Weight 380-400gsm



Width 280cm



Openness
Factor 0%



Composition
100% Polyester



Anti-Bacterial
Anti-Static
DIN EN 1149-1/2



Thickness
0.65mm



Fire Rating
NFPA
701 / BS5867 / M1




Suitable for
Humid
Environments



CSB 01



CSB 02



CSB 04



CSB 50



CSB 51



CSB 52



CSB 53



CSB 54



CSB 55



CSB 56



CSB 60



CSB 61



CSB 62



CSB 63



CSB 70



CSB 71



CSB 72



CSB 80



CSB 81



CSB 82